



PHS Service Grommets

PHS service grommets are made from a strong and flexible EPDM. They're specifically designed for quick and secure sealing of pipes penetrating both the internal airtight vapour control layer & external waterproof/windtight layer.

PHS grommets provide a tight, flexible fit that prevents the uncontrolled flow of water vapour and air, allowing for greater airtight levels and prevention of interstitial condensation.

PHS grommets are bonded to the appropriate substrate with PHS Argo tape or another suitable universal joining tape.

Application

Before application of PHS service grommets, ensure that the application area is clean, dry, grease and dust free.

Adhesion to frozen surfaces isn't possible and apply only in the appropriate application temperature

PHS Argo tape provides a permanent bond between the grommet and substrate. If bonding to MDF, precondition the surface with a suitable primer to ensure the best possible bond.



Grommets Sizes

PHS50	50-65mm pipe diameter	180x180mm perimeter	2mm thickness
PHS100	100-110 pipe diameter	245x245mm perimeter	1.5mm thickness

Technical Data

Material	EPDM
Temperature Resistance	-30C to +100C
Application Temperature	-10C to +40C
Life Expectancy	60 years +
Usage	Internal & External
Colour	Black

UK Passive House Systems Ltd.
 Epping, Essex, CM16 6TH
 Tel: 08454591500
 Website www.passivehousesystems.co.uk



Ireland. Passive House Systems.
 Business Park, Ballincollig, Co. Cork, Ireland
 Tel: (00353) 021 4289407
 Website www.passivehousesystems.ie

Passive House Systems products are used by a very diverse customer base for a wide range of technical and industrial applications. The demands made on our products vary considerably from application to application. We strongly advise users to test the products suitability for their own particular requirement. All data and recommendations contained in this Technical Data Sheet are based on our own test results and practical experience and are aimed at helping customers select the appropriate product. This information is provided without liability. We reserve the right to change the technical specification without prior notice. Samples are available free of charge. Our sales team is also available to assist customers with their help.