

Gerband 586 Joining Tape

Brand: Gerband

Gerband 586 is a pliable and stretchable PE-film sealing tape with a moisture resistant, polyacrylate adhesive of extremely high tack. It offers permanent adhesion as well as outstanding ageing resistance. The slight elasticity in connection with tear-resistant thread reinforcement makes the Gerband 586 universally suitable for achieving airtightness as well as sealing many types of surfaces.

TECHNICAL DETAILS

| | |
|-------------------------------|--|
| Base Material: | LD-polyethylene foil, stretchy, green |
| Adhesive: | Acrylate dispersion, solvent-free |
| Adhesive middle layer: | Polyester lattice layer |
| Covering material: | Silicon paper, brown |
| Thickness (without covering): | 0.28mm |
| Adhesive layer: | 210g / m ² |
| Adhesive strength: | 35N / 25mm DIN EN 1939 |
| Temperature resistance: | 40°C to 80°C |
| UV resistance: | Max. 3 months |
| Durability against ageing: | Excellent |
| Moisture resistance: | Excellent |
| Processing temperature: | Recommended from 5°C to 40°C, possible from -10°C |
| Sizes & Packaging: | 50mm x 25m 60mm x 25m 75mm x 25m 100mm x 25m 150mm x 25m |

APPLICATION

Gerband 586 Airtight Tape might be used indoors for the airtight bonding of wind and vapour barriers. It can be used in nonvisible areas of building components and also on impact resistant plastics (pipes, windows), wood or metal.



**PASSIVE
HOUSE
SYSTEMS**

Passive House Systems
Brickfield House Business Centre
Thornwood
Epping CM16 6TH
United Kingdom

Tel: 0333 880 2347
info@passivehousesystems.co.uk
www.passivehousesystems.co.uk