

PHS Service Grommets

Brand: Passive House Systems

PHS Service Grommets provide a tight, flexible fit that prevents the uncontrolled flow of water vapour and air, allowing for greater airtight levels and prevention of interstitial condensation. They are specifically designed for quick and secure sealing of pipes penetrating both the internal airtight vapour control layer & external waterproof/windtight layer. PHS grommets are bonded to the appropriate substrate with PHS Argo tape or another suitable universal joining tape.

TECHNICAL DETAILS

Material:	EPDM	
Total thickness:	(DIN EN 1942)* 0.35 mm	
Tensile strength:	(DIN EN 14410)* >150 N / 25 mm	
Elongation at break:	(DIN EN 14410)* 3% to 5 % lengthwise	
Adhesion:	(DIN EN 1939)* _40 N / 25 mm	
Temperature range:	-40°C to 80°C	
Sizes & Packaging:	4-8mm 50-60mm 120-130mm	25-35mm 100-110mm 150-165mm

APPLICATION

Before application of PHS service grommets, ensure that the application area is clean, dry, grease and dust free. Adhesion to frozen surfaces isn't possible. Apply only in the appropriate application temperature.



**PASSIVE
HOUSE
SYSTEMS**

Passive House Systems
Brickfield House Business Centre
Thornwood
Epping CM16 6TH
United Kingdom

Tel: 0333 880 2347
info@passivehousesystems.co.uk
www.passivehousesystems.co.uk